

Schock Absorbers

Product image	Prod. Name	Prod.ID	Fitting - Spring - Fitting Head Options	Head Prod.ID	Length/Weight	Duct min- max D _{in} (Calibration %)	Compatible Sondes				
	IV343	V14343	M3.5 - Ø4.0mm - M3.5	---	67mm / 2.2g	6mm - 8mm	X				
	IV343-48	V14350	IV343 + head Ø4.8mm	T20840	76mm / 3.4g	6mm (80%) - 8mm (60%)	X				
	IV343-64	V14355	IV343 + head Ø6.4mm	T20841	82mm / 6.0g	8mm (80%)	(X)				
	IV565 v2	V14567	M5 - Ø6.4mm - M5	--- 1)	49mm / 6.3g	8mm - 12mm		X	X	X	
	IV566 v2	V14568	M5 - Ø6.4mm - M6	---	46mm / 6.9g	8mm - 12mm		X	X	X	
	IV566-66	V14571	IV566 + head Ø6.6mm	T20845	57mm / 9.0g	8mm (83%) - 10mm (66%)		X	X		
	IV566-80	V14576	IV566 + head Ø8.0mm	T20842	61mm / 13g	10mm (80%) - 12mm (67%)		X	X	X	
	IV566-96	V14581	IV566 + head Ø9.6mm	T20843	67mm / 19g	12mm (80%)		(X)	(X)	X	
	IV696 v2	V14697	M6 - Ø9.0mm - M6	---	52mm / 15g	12mm - 20mm				X	X
	IV696-96	V14701	IV696 + head Ø9,6mm	T20843	72mm / 27g	12mm (80%) - 14mm (69%)				X	X
	IV696-112	V14706	IV696 + head Ø11.2mm	T20844	78mm / 36g	14mm (80%) - 16mm (70%)				(X)	X
	IV696-128	V14711	IV696 + head Ø12.8mm	T20839	83mm / 25g	16mm (80%) - 20mm (64%)				(X)	X

Flexible Mountings and Adapters

Product image	Prod. Name	Prod.ID	Fitting - Spring - Fitting	Length/Weight	Duct min- max D _{in}	Compatible Sondes					
	FM55	V14805	M5 - Ø6.4mm - M5F	55mm / 6.8g	8mm - 12mm		X	X	X	(X)	
	FM56	V14800	M5 - Ø6.4mm - M6F	55mm / 7.2g	8mm - 12mm		X	X	X	(X)	
	PL18-FM	V14194	PL18 - Ø18mm - M12F & M6F	97mm / 90g	21mm						X
	PL-MSA5	V14057	M12 - M5F	39mm / 26g	---						X

1) No head available from Vesala. Customers can use their own head/ accessory with M5 fitting.

2) Flexible accessory to protect M5 sondes during push rod use. FM56 operates also as an M5 to M6 adapter. Smallest recommended duct diameter depends on the sonde being used.

3) PL18-FM includes a battery compartment for PL18 sondes

4) Minimum 9mm duct size is recommended.

Example of use:



MPL6-33M5F sonde with the IV566-66 shock absorber, ready to be used to calibrate 8mm ducts with 80% diameter ratio or 10mm ducts with 66% ratio.

Sondes & Prod.ID

X = Recommended
(X) = Compatible but not recommended.



Shock absorbers are special accessories to Vesala's NanoSonde, MicroSonde and MiniSonde, intended for duct tracing and calibration together with a blowing machine. They considerably decrease risk of sonde damage during jetting by absorbing the excessive energy when the sonde hits an object. Hence it is recommended to use shock absorbers when possible.

All shock absorbers include a base part with a spring with two threaded fittings. First thread is to mount the base to the sonde, the other for a calibrator head or push rod. A variety of shock absorbers and calibrator heads are readily available for different sonde models and duct sizes. The table on the left shows all compatible combinations.

Even if customers prefer to use their own calibrator heads, it is important to choose the right shock absorber according to the sonde model and duct size, and use a Vesala SC39 Sonde Catcher at the duct end. Vesala sales dept. will gladly help you to choose the right accessories for your sondes.

Flexible mountings are for attaching sondes to a push rod. Especially at duct corners added flexibility makes sonde traveling smoother and reduces risk of damage.

www.vesala.fi

H. VESALA Oy

Peräsimentie 1
FI-03100 NUMMELA
FINLAND

Tel. +358 44 200 2005

Email: sales@vesala.fi